



Effective
Monitoring Tools



50 Years +
of Industry Experience



Technical
Support



Security Approved
Support Teams



Cyber Certified

Iridium GO! Exec

The Iridium GO! Exec is the first portable touchscreen-enabled satellite access terminal and creates a reliable, high quality, global connection for voice and data communications for your smart devices. This rugged, compact device dramatically extends the capabilities of any smartphone, laptop, or tablet by creating a satellite-backed Wi-Fi hotspot – anywhere on the planet.



Small form, Small Team or Individual Connectivity

Iridium Go! Exec provides a truly global, easy to use connectivity pack enabled by the Iridium Certus 100 service supporting messaging, email, phone calls and light web browsing over the Iridium Go! Exec app for up to 5 devices up to 30 metres away, along with two additional voice lines direct from the device. Small enough to fit in a backpack or small pouch, and like other Iridium devices tough enough to withstand rain, sand, dust and rough use. Voice and IP connectivity on the move, on the pause or at the halt, the Iridium Go! Exec can support a small team or individual user anywhere in the world for liaison, reconnaissance, senior user or discrete tasks.

Simple operation

Simply raise the integrated antenna and the battery-powered unit connects quickly and automatically to the Iridium Certus 100 service to create an anywhere Wi-Fi hotspot. The Iridium GO! Exec comes with multiple ports, 2 USB-C's, an external ethernet port, an external antenna port, and an external GPS port. An external antenna kit will be sold separately. It also comes with an SOS button which can contact whatever number you set but the default setting is the IERCC (International Emergency Response Coordination Centre) to help you in a potential emergency (registration required).



Features

- Modern and compact
- Built in secure Wi-Fi
- Built in microphone and speaker
- Multiuser access (2 voice calls / 5 data connections simultaneously)
- App/Web filtering included to restrict access where desired
- Easy to setup, power on and raise antenna
- SOS button contacting IERCC (default contact, registration required)



Specifications

Dimensions (L x W x H mm)	203 x 203 x 25
Weight (g)	1200
Data	88Kpbs download / 22Kbps upload
Connectivity:	External antenna connector External ethernet port USB-C (power)
Operating Temperature:	-20 to +50 °C (including battery)
Storage Temperature:	-20 to +60 °C (including battery)
Ingress Protection:	P65/MIL-STD 810H
Battery	Up to 6 hours operating Up to 24 hours standby
Service	Iridium Certus 100
Package Includes	Iridium GO! Exec device Protective Cover USB-C charging Wall charger (with international plug kit) DC Adapter (car charger) User manual



United Kingdom (HQ)	Tel: +44 1737 648 800	Email: enquiries@nsslglobal.com	Denmark	Tel: +45 3670 3603	Email: info.dk@nsslglobal.com
Germany Hamburg	Tel: +49 40 682770	Email: info@nsslglobal.com	Poland	Tel: +48 22 404 78 64	Email: sales.pl@nsslglobal.com
The Netherlands	Tel: +31 (0)85 073 4010	Email: info@nsslglobal.com	Singapore	Tel: +65 6358 3991	Email: enquiries.sg@nsslglobal.com
Sweden	Tel: +46 31 990 777	Email: enquiries.sweden@nsslglobal.com	USA	Tel: +1 504 800 6290	Email: enquiries.usa@nsslglobal.com
Norway	Tel: +47 67 535 337	Email: support.no@nsslglobal.com			